



**Pride Machine Tools Pvt. Ltd.**  
Purebred Performers

## Torpedo

[<< Back](#)



### Description

- Compact footprint
- LM guide Ways on both axes
- 30 slant bed for better chip disposal

SPECIFICATION			
	UNIT	TORPEDO-5	TORPEDO-6
<b>CAPACITY</b>			
Swing Over bed	mm	440	440
Max.turning dia	mm	160	160
Max.tuning lenth	mm	220	220
Standard chuck size	mm	135	165
<b>SLIDES</b>			
X Axis stroke	mm	80	80
Z Axis storke	mm	240	240
Rapid rates	mm/min	20000	20000
<b>SPINDLE</b>			
Spindle size		A2-4	A2-5
Spindle bore	mm	38	47
Spindle front bearing dia	mm	60	80
Max bar capacity*	mm	18	25
Spindle speed range	RPM	50-4000	50-4000
Spindle motor power	KW	3.7/5.5	5.5/7.5
<b>TURRET</b>			
Size		BTP-63	BTP-63
No.Of.stations		8	8
Max.boring dia	mm	32	32
Tool size	mmxmm	20*20	20*20
<b>TAIL STOCK</b>			
Quil dia	mm	60	60
Quill stroke	mm	80	80
Quill bore taper	mm	MT-4	MT-4
<b>ACCURACY</b>			
Positioning	mm	0.005	0.005
Repeatability	mm	0.003	0.003
Machine Weight(approx)	kg	2200	2200
Machine dimension	mm	1950*1400*1700	1950*1400*1700
CNC System**		Fanuc	Fanuc

[Click Here to Enquire About This Product](#)

[<< Back](#)